



UL Model#: FZ-CV03

<b>Fabric:</b>	<b>High Visibility Trim:</b>
<ul style="list-style-type: none"> <li>-7oz(240g/m<sup>2</sup>) FR fabric</li> <li>-100% Cotton</li> </ul>	<ul style="list-style-type: none"> <li>-Not applicable</li> </ul>
<b>Garment construction:</b>	<b>PPE Standards Met:</b>
<ul style="list-style-type: none"> <li>-Aramid high tenacity FR thread</li> <li>-All metal thermally protected from the skin</li> <li>-Bar-tacked at all stress points</li> <li>-Protective shirt collar</li> <li>-Heavy duty brass zipper on aramid tape</li> <li>-Two-way #5 zipper at CF</li> <li>-Storm guard over front zipper with snaps closure</li> <li>-Action back for mobility</li> <li>-Side elasticized waist</li> <li>-Separate arm cuffs with snap closures</li> <li>-Snaps at leg bottom</li> </ul>	<ul style="list-style-type: none"> <li>-Protective flame retardant suits described in this technical standard are used in noxious and hazardous environments must meet the following safety and visibility standards:</li> <li>-CAT 2</li> <li>-ATPV 9 cal/cm<sup>2</sup> (electric arc flash rating)</li> <li>-ASTM F1959, ASTM F1506, NFPA 70E</li> <li>-Material is UL Recognized per NFPA 2112-2023 (UL file MH60111, UL model C10007)</li> <li>-OEKO-TEX Standard 100</li> </ul>
<b>Pockets:</b>	<b>Color reference:</b>
<ul style="list-style-type: none"> <li>-2 flap chest patch pockets with snaps closure, pencil slot on both pockets</li> <li>-2 waist patch pockets with side access</li> <li>-2 rear hip patch pockets</li> <li>-Pen pocket on left sleeve</li> <li>-Tool pocket on right leg</li> </ul>	